

应用场所 Application

- 广泛应用于海洋工程各类作业平台、各类化学品、天然气运输船、危险品码头等危险区域作监控之用；
- 可在潮湿、振动、腐蚀等恶劣环境中可靠工作；
- 适用于爆炸性危险环境1区、2区等场所。
- Widely used for the supervisory control on various marine platforms, chemical tankers, LNG ships and hazardous cargo wharfs, etc..
- Can reliably work in severe environment exposed in moisture, vibration or corrosion;
- Explosive hazardous atmosphere Zone 1, Zone 2.



产品特性 Product features

- 防爆手持照明摄像终端在智能视频监控系统中作为移动终端使用；实现现场视频图像感知上传等功能；
- 产品适合危险爆炸区域巡检人员使用，设备具有照明功能、信号灯功能、定位功能、实时图传及实时视频等功能；
- 全网通：5G、4G、3G、2G 信号；2.4G/5G双频WIFI信号；
- 产品本安防爆设计，配备10000mAh大容量本安电池，超长续航时间。
- Explosion-proof handheld lighting camera terminal is used as mobile terminal in intelligent video surveillance system; to realize the on-site video image perception upload and other functions.
- The product is suitable for inspection personnel in dangerous explosion areas. The equipment has lighting function, signal light function, positioning function, real-time picture transmission and real-time video function.
- All Netcom: 5G, 4G, 3G, 2G signal; 2.4G/5G dual-band WIFI signal.
- The product adopts intrinsic safety explosion-proof design, equipped with 10000mAh large capacity safety battery, super long life.

技术参数 Technical parameters

防爆标志 Ex-Mark	Ex ib IIC T4 Gb
防护等级 Protection grade	IP66
防腐等级 Anticorrosive grade	WF2
显示屏 Display screen	1.54寸液晶屏 1.54 inch LCD screen
电池 Battery	3.7V 10000mAh
LED功率 LED power	3W/1W切换 Switch
信号灯 Signal light	支持红绿信号灯(III型) Support red and green signal lights (Type III)
摄像头 Camera	1300万像素(I型)、2000万像素(III型) 13 megapixels (Type I), 20 megapixels (Type III)
接口 Interface	支持USB接口 Support USB interface
内存扩展 Memory expansion	I型标配64G(最大128G); III型标配128G(最大128G) Type I comes standard with 64G(Max. 128G); Type III Standard 128G(Max 128G)
安装方式 Installation mode	固定支架(可选) Fixed support (optional)
外形尺寸 Outline dimension	I型: 267(长度)×Φ60(头部)×Φ34mm(筒身); III型: 258(长度)×Φ58(头部)×Φ34mm(筒身) Type I: 267(length)×Φ60(head)×Φ34mm(barrel body); Type III: 258(Length)×Φ58(head)×Φ34mm(barrel body)